BORDER SAFETY WEARS

PRODUCT DATASHEET

DESIRE

Product Code: BFP 2015

Safety Shoe | EN ISO 20345:2022 | S3 SR FO HRO LG

Sizes: EU 39-46











AREA OF APPLICATION

Recommended for construction, oil & gas, foundries, steel plants, heavy engineering, manufacturing, logistics, infrastructure projects, and other industrial environments where protection against impact, puncture, heat, slip, and fuel oil hazards is required.

TECHNICAL SPECIFICATIONS

Safety Category	S3 SR FO HRO LG
Upper Material	Breathable Leather
Toe Cap	Epoxy-Coated Steel Toe Cap (200 Joules)
Midsole	Epoxy-Coated Steel Plate (1100N Penetration Resistance)
Outsole	Dual-Density Heat Resistant PU Outsole (Up to 200°C)
Sole Construction	Direct Injection Moulded
Lining	Highly Abrasion Resistant Fabric
Collar	Padded Collar Below Tongue for Extra Comfort
Insole	Removable Antistatic Footbed with Fabric Lining
Height, Shaft/Upper	6 Inches
Colour	Black
Origin	China
Design	As per ADNOC Specification
Weight	500gms (42 size, single leg)

BORDER®
SAFETY WEARS

KEY FEATURES

- 200 Joule Epoxy-Coated Steel Toe Protection
- 1100N Epoxy-Coated Steel Plate Penetration Resistance
- Dual-Density Heat Resistant Outsole (Up to 200°C)
- Slip Resistant (SR)
- Fuel Oil Resistant (FO)
- Heat Resistant Outsole (HRO)
- Ladder Grip (LG)
- Breathable Leather Upper
- Highly Abrasion Resistant Fabric Lining
- Removable Antistatic Footbed
- Direct Injection Moulded Sole Construction
- Industrial Grade Safety Footwear

PROTECTIVE FEATURES

Epoxy-Coated Steel Toe Cap (200J)	Provides superior protection against impact and compression hazards in demanding industrial environments.
Epoxy-Coated Steel Plate (1100N)	Protects the foot against puncture hazards caused by nails, metal debris, and sharp objects.
Heat Resistant Outsole (HRO)	Dual-density outsole withstands contact heat up to 200°C, making it suitable for high-temperature working environments.
Slip Resistant Outsole (SR)	Provides reliable traction on ceramic and industrial flooring to reduce the risk of slips.
Fuel Oil Resistant Outsole (FO)	Designed to resist deterioration caused by exposure to fuel oils and industrial lubricants.
Ladder Grip (LG)	Special outsole profile improves stability and grip while working on ladders.
Abrasion Resistant Construction	Breathable leather upper and durable outsole provide long service life under demanding working conditions.

CERTIFICATIONS

- EN ISO 20345:2022
- S3 SR FO HRO LG
- CE Marked

SR	Slip Resistance
FO	Fuel Oil Resistant Outsole

HRO (upto 200°C)	Heat Resistant Outsole
LG	Ladder Grip

INDUSTRIES

- Construction
- Oil & Gas
- Foundries
- Steel Plants
- Heavy Engineering
- Manufacturing
- Logistics
- Infrastructure Projects
- Mining
- General Industrial

STORAGE & MAINTENANCE

- Store footwear in a cool, dry place away from direct sunlight.
- Clean with a soft brush or damp cloth after use.
- Do not use harsh chemicals or strong solvents.
- Allow footwear to dry naturally after exposure to moisture.
- Inspect footwear regularly and replace if excessive wear or damage is observed.

WARRANTY

6 MONTHS MANUFACTURING WARRANTY.
Warranty covers manufacturing defects under normal working conditions.