BORDER SAFETY WEARS

PRODUCT DATASHEET

PROTEX

Product Code: BFP 2018

Safety Shoe | EN ISO 20345:2022 | S3 SR FO

Sizes: EU 39-46











AREA OF APPLICATION

Recommended for construction, infrastructure, manufacturing, logistics, warehousing, engineering, maintenance, and industrial workplaces where protection against impact, puncture, slip, and fuel oil hazards is required.

TECHNICAL SPECIFICATIONS

Safety Category	S3 SR FO
Upper Material	Embossed Breathable Leather
Toe Cap	Epoxy-Coated Steel Toe Cap (200 Joules)
Midsole	Epoxy-Coated Steel Plate (1100N Penetration Resistance)
Outsole	Dual-Density PU & Rubber
Sole Construction	Direct Injection Moulded
Lining	Highly Abrasion Resistant Fabric
Eyelets	Metallic Anodized D-Ring Eyelets
Laces	High-Quality Braided Shoelace
Insole	Removable Antistatic Footbed with Fabric Lining
Colour	Black
Origin	China

KEY FEATURES

- EN ISO 20345:2022 & ASTM F2413-21 Certified

BORDER®
SAFETY WEARS

- 200 Joule Epoxy-Coated Steel Toe Protection
- 1100N Epoxy-Coated Steel Plate Penetration Resistance
- Dual-Density PU & Rubber Outsole
- Slip Resistant (SR)
- Fuel Oil Resistant (FO)
- Premium Embossed Breathable Leather Upper
- Highly Abrasion Resistant Fabric Lining
- Metallic Anodized D-Ring Eyelets
- High-Quality Braided Shoelaces
- Removable Antistatic Footbed
- Direct Injection Moulded Sole Construction
- Industrial Grade Safety Footwear

PROTECTIVE FEATURES

Epoxy-Coated Steel Toe Cap (200J)	Provides reliable protection against impact and compression hazards in demanding industrial workplaces.
Epoxy-Coated Steel Plate (1100N)	Protects against puncture hazards from nails and other sharp objects underfoot.
Slip Resistant Outsole (SR)	Dual-density PU & Rubber outsole provides dependable grip on industrial flooring and work surfaces.
Fuel Oil Resistant Outsole (FO)	Designed to resist deterioration caused by exposure to fuel oils and industrial lubricants.
Abrasion Resistant Construction	Premium embossed breathable leather and durable outsole provide extended service life in demanding environments.
Shock Absorbing Heel	Helps reduce foot fatigue and enhances comfort during prolonged use.

CERTIFICATIONS

- EN ISO 20345:2022
- ASTM F2413-21
- S3 SR FO
- CE Marked

200 Joule Steel Toe Protection	
Closed Heel Area	
Anti-Static Properties	
Energy Absorption in Heel Area	

Steel Plate Penetration Resistance	
Water Resistant Upper	
Slip Resistance (SR)	
Fuel Oil Resistant Outsole (FO)	

INDUSTRIES

- Construction
- Manufacturing
- Engineering
- Oil & Gas
- Warehousing
- Logistics
- Infrastructure
- Maintenance
- General Industrial

STORAGE & MAINTENANCE

- Store in a cool and dry place.
- Avoid prolonged exposure to direct sunlight.
- Clean with a soft brush or damp cloth.
- Do not use harsh chemicals or solvents.
- Allow footwear to dry naturally before storage.
- Replace footwear if excessive wear or damage is observed.

WARRANTY

6 MONTHS MANUFACTURING WARRANTY. Warranty covers manufacturing defects under normal working conditions.