BORDER SAFETY WEARS

PRODUCT DATASHEET

BFP2044 SAFETY BOOT

Product Code: BFP 2044

Safety Boot | EN ISO 20345:2022 | S1P SR FO HRO

Sizes: EU 39-47











AREA OF APPLICATION

Recommended for construction, manufacturing, warehousing and general industrial environments where impact, puncture, slip, fuel-oil and contact-heat protection is required.

TECHNICAL SPECIFICATIONS

Safety Category	S1P SR FO HRO
Upper Material	Microfiber Leather
Lining	Soft Mesh Fabric
Toe Cap	Epoxy-Coated Widened Steel Toe Cap (200 Joules)
Midsole	Epoxy-Coated Steel Plate (1100N Puncture Resistance)
Sole Construction	Injection Moulded
Insole	Removable Moulded EVA
Outsole	Single-Density PU
Colour	Tan
Origin	China

KEY FEATURES

- EN ISO 20345:2022 Certified
- 200J Steel Toe Cap
- 1100N Steel Puncture-Resistant Midsole
- Microfiber Leather Upper

BORDER SAFETY WEARS

- Single-Density PU Outsole
- Slip Resistant (SR)
- Fuel Oil Resistant (FO)
- Heat Resistant Outsole (HRO)
- Antistatic
- Shock Absorbing Heel Design

PROTECTIVE FEATURES

Steel Toe Cap (200J)	Protection against impact and compression hazards.
Steel Midsole (1100N)	Puncture resistance against sharp objects.
Slip Resistant Outsole (SR)	Reliable grip on industrial flooring.
Fuel Oil Resistant Sole (FO)	Resistant to degradation from fuel oil exposure.
Heat Resistant Outsole (HRO)	Withstands contact heat up to 300 C.
Shock Absorption	Reduces impact stress in the heel area.

CERTIFICATIONS

- EN ISO 20345:2022
- S1P SR FO HRO
- CE Marked

S1P	Antistatic, energy absorption, closed heel & steel puncture-resistant midsole.
SR	Slip resistance.
FO	Fuel oil resistant outsole.
HRO	Heat resistant outsole to 300 C.

INDUSTRIES

- Construction
- Oil & Gas
- Manufacturing
- Logistics
- Warehousing
- Engineering
- Maintenance

STORAGE & MAINTENANCE

- Store in a cool and dry location.

- Avoid prolonged exposure to direct sunlight.
- Clean with a soft brush or damp cloth.
- Do not use strong solvents or harsh chemicals.
- Allow footwear to dry naturally after use.
- Replace footwear if excessive wear or damage is observed.

WARRANTY

6 MONTHS MANUFACTURING WARRANTY. Warranty covers manufacturing defects under normal working conditions. Warranty is void if products are subjected to excessive heat, chemicals, cement water, bleach or water.