BORDER SAFETY WEARS

PRODUCT DATASHEET

RIGGER BOOT BSW BROWN

Product Code: BSW 0501

Safety Rigger Boot | EN ISO 20345:2022 | S1P SR FO HRO

Sizes: EU 39-46











AREA OF APPLICATION

Recommended for construction, oil & gas, manufacturing and heavy industrial environments where impact, puncture, slip, fuel-oil and contact-heat protection is required.

TECHNICAL SPECIFICATIONS

Safety Category	S1P SR FO HRO
Upper Material	Breathable Cow Split Leather
Lining	Abrasion-Resistant Mesh
Toe Cap	Epoxy-Coated Steel Toe Cap (200 Joules)
Midsole	Epoxy-Coated Steel Plate (1100N Puncture Resistance)
Insole	Removable Antistatic Fabric-Lined
Outsole	PU (Heat Resistant to 300 C)
Sole Construction	Direct Injection Moulded
Colour	Brown
Origin	China

KEY FEATURES

- EN ISO 20345:2022 Certified
- 200J Steel Toe Cap
- 1100N Steel Puncture-Resistant Midsole
- Pull-On Rigger Design

BORDER®
SAFETY WEARS

- Breathable Leather Upper
- PU Outsole (Heat Resistant 300 C)
- Slip Resistant (SR)
- Fuel Oil Resistant (FO)
- Heat Resistant Outsole (HRO)
- Antistatic

PROTECTIVE FEATURES

Steel Toe Cap (200J)	Protection against impact and compression hazards.
Steel Midsole (1100N)	Puncture resistance against sharp objects.
Slip Resistant Outsole (SR)	Reliable grip on industrial flooring.
Fuel Oil Resistant Sole (FO)	Resistant to degradation from fuel oil exposure.
Heat Resistant Outsole (HRO)	Withstands contact heat up to 300 C.
Antistatic	Dissipates static charge build-up.
Shock Absorption	Reduces impact stress in the heel area.

CERTIFICATIONS

- EN ISO 20345:2022
- S1P SR FO HRO
- CE Marked

S1P	Antistatic, energy absorption, closed heel & steel puncture-resistant midsole.
SR	Slip resistance.
FO	Fuel oil resistant outsole.
HRO	Heat resistant outsole to 300 C.

INDUSTRIES

- Construction
- Oil & Gas
- Manufacturing
- Logistics
- Warehousing
- Engineering
- Maintenance

BORDER®
SAFETY WEARS

STORAGE & MAINTENANCE

- Store in a cool and dry location.
- Avoid prolonged exposure to direct sunlight.
- Clean with a soft brush or damp cloth.
- Do not use strong solvents or harsh chemicals.
- Allow footwear to dry naturally after use.
- Replace footwear if excessive wear or damage is observed.

WARRANTY

6 MONTHS MANUFACTURING WARRANTY. Warranty covers manufacturing defects under normal working conditions. Warranty is void if products are subjected to excessive heat, chemicals, cement water, bleach or water.